



The Power of IP to Enhance Business Communications

Take enterprise-wide communication to a whole new level with an IP communication system that integrates your voice, data networking, and application solutions. One that combines the advantages of network-based telephony and the features of PBX systems, as well as valuable options like Voice Mail/Auto Attendant/Unified Messaging, Automatic Call Distribution, Strata Net multiple system networking, FeatureFlex®

adaptability/customization tools, and more to improve your business' overall productivity and customer service.

Strata® CIX™ systems are designed to work exactly as you need today, in one or multiple locations, while enabling you to grow and add other capabilities in the future. The Strata CIX is the ultimate, modular, scalable, networkable communication system for your business.

SPECIFICATIONS

Model	Strata CIX200			
Capacities	96 trunks or 160 endpoints and combinations up to 192 total.			
Chassis Measurements Base Cabinet	Width	Height	Depth	Weight
Metric	440 mm without bracket 483 mm with bracket	89 mm	410 mm	7.2 kg
English	17.3 in. without bracket 19 in. with bracket	3.5 in.	16.1 in.	16 lbs.
Chassis Measurements Expansion Cabinet	Width	Height	Depth	Weight
Metric	440 mm without bracket 483 mm with bracket	89 mm	410 mm	7.2 kg
English	17.3 in. without bracket 19 in. with bracket	3.5 in.	16.1 in.	16 lbs.
Power Supply Unit (PSU)	Initially Built-in (one per cabinet).			
Primary AC Power	Input AC 120VAC, 4.0 amps maximum. AC Frequency Single-phase (45Hz - 65Hz). 480 watts per cabinet (maximum).			
Power Backup	An Uninterruptible Power Supply (UPS) is required for power backup on a CIX200. The UPS is similar to the ones used for computer systems and networking equipment.			
Chassis Installation	19" Rack-mount (preferred) or Table top. Standard 19" rack-mounting, IEC297-1 (EIA RS 310-D), 465.1mm (front face screw pitch-width).			
Compliance	Safety: UL EMC: FCC Part 15 Class A (Subpart A) HAC and Volume Control: FCC Part 68 Network safety: TIA-968-2-A			
FCC Registration	PBX: CJ6PF03BDTCHS192 Hybrid: CJ6MF03BDTCHS192 Key: CJ6KD03BDTCHS192			

SPECIFICATIONS

Operating Temperature	32~104° F (0~40° C)
Operating Humidity	20~80% relative humidity without condensation
Storage Temperature	-4~140° F (-20~60° C)
Voice Mail Compatibility	Strata Media Application Server, Stratagy® ES, iES32, iES16, IVP8
Trunk Compatibility	Analog: Loop or ground start, DID, E&M Digital: T1, ISDN PRI and BRI IP: Strata Net IP Networking E911: CAMA and ISDN PRI
IP Telephone Compatibility	Toshiba 2000-Series MEGACO+ models: <ul style="list-style-type: none"> > IPT2010-SD full-duplex speakerphone with 10 programmable buttons and 2-line x 24-character LCD. > IPT2020-SD full-duplex speakerphone with 20 programmable buttons and 2-line x 24-character LCD. > IPT2008-SDL full-duplex speaker phone with 8 programmable buttons and large 144 x 128 pixel display with HTML support. > 802.3af Power-over-Ethernet compliant. > Ethernet switch for PC connection to your IP Networking. > Uniden UIP 200 SIP Telephone.
Digital Telephone Compatibility	Toshiba 5000-Series models: <ul style="list-style-type: none"> > DP5008 single-line telephone with one programmable button. > DP5018-S speakerphone with 10 programmable buttons. > DP5022-SD speakerphone with 10 programmable buttons and 4-line x 24-character LCD with contrast adjustment. > DP5122-SD speakerphone with 10 programmable buttons and 4-line x 24-character Backlit LCD with contrast adjustment. > DP5032-SD speakerphone with 20 programmable buttons and 4-line x 24-character LCD with contrast adjustment. > DP5132-SD speakerphone with 20 programmable buttons and 4-line x 24-character Backlit LCD with contrast adjustment. > DP5130-SDL speakerphone with 10 programmable LCD-label buttons and large 9-line x 24-character Backlit LCD with contrast adjustment.
Analog Device Compatibility	Dealer-supplied standard telephones with or without Caller ID, FAX machines, modems, etc.
Answer Position Options	LM5110 Add-On Module with 10 programmable Backlit LCD-label buttons. KM5020 Add-On Module with 20 programmable buttons. DDM5060 DSS/BLF Console with 60 programmable buttons. Strata PC Attendant Console.
User Mobility Options	SoftIPT® soft phone client on laptop or tablet PC via wi-fi W-LAN. SoftIPT soft phone client on PDA via wi-fi W-LAN. Wireless IP telephone support via wi-fi W-LAN. Cordless digital telephone.
System Administration	Browser-based unified administration of PBX and voice mail functions. eManager® installation/maintenance for technicians and administrators. eMonitor monitoring of alarm conditions from multiple Strata CIX systems. My Phone Manager® personal administration for individual users. Traffic measurement reports stored on local SD flash memory card.
Standard System Features	Over 300 standard telephony features to provide the functionality you need.
Advanced Application Options	Add valuable options like Voice Mail/Auto Attendant, Unified Messaging, Automated Speech Recognition, Text-To-Speech, Interactive Voice Response, Automatic Call Distribution and Reporting, Voice Over Internet Protocol, Strata Net multiple system networking, Info Manager® Web-based telephone applications, FeatureFlex adaptability/customization tools, uniform call distribution, centralized network SMDR, and more.
Multi-system Networking	Strata Net networking of up to 128 nodes via IP or ISDN PRI.
Feature Customization	FeatureFlex adaptability tools for feature creation/customization.

Toshiba America Information Systems, Inc., Telecommunication Systems Division

9740 Irvine Blvd., Irvine, CA 92618-1697 (949) 583-3700 www.telecom.toshiba.com

© 2007 Toshiba America Information Systems, Inc., Telecommunication Systems Division. Printed in U.S.A. Strata is a registered trademark of Toshiba Corporation. Stratagy is a registered trademark of Toshiba America Information Systems, Inc. Specifications subject to change without notice. Some features require optional hardware/software to support full capabilities.

Literature Order #: TSD-CIX-BR-200-DS-VD/4500118